



This page includes  
Solid Tires | PRESS-ON BANDS

# PRESS-ON BANDS

TYRE SPECIFICATIONS (INCHES)													
Tyre load capacity (kg) at max. speed mph (kmph)													
IMPERIAL SIZE			Counterbalanced-fork-lift-trucks, up to								On Other Vehicles, up to		
TYRE SIZE (INCHES)	TYRE SIZE (MM)	TREAD			6 mph (10 mph)		10 mph (16 mph)		16 mph (25 mph)		3.75 mph	6 mph	10 mph
		PNS 85	PNM 85	PNT 85	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 kmph	10 kmph	16 kmph
<b>4"</b>													
8 1/2x4x4	216/102-102	•			700	575	625	525	525	415	750	550	500
<b>5"</b>													
9x5x5	229/127-127	•	•		960	790	960	790	855	720	960	790	720
<b>6 1/4"</b>													
10x3x6 1/4	254/76-159	•			590	485	525	440	-	-	700	460	420
10x4x6 1/4	254/102-159	•			780	640	695	585	585	460	835	610	585
10x4 3/4x6 1/4	254/121-159	•			970	795	865	725	705	575	1,035	760	690
10x5x6 1/4	254/127-159	•	•		1,015	835	905	760	760	600	1,100	805	760
10x6x6 1/4	254/152-159	•	•		1,270	1,040	1,135	950	925	755	1,360	995	910
<b>6 1/2"</b>													
10x4x6 1/2	254/102-165	•	•		780	640	780	640	695	585	780	640	585
10x4 3/4x6 1/2	254/121-165	•			950	780	845	710	690	565	1,025	750	685
10x5x6 1/2	254/127-165	•	•		1,010	830	1,015	835	905	760	1,015	835	760
10x6x6 1/2	254/152-165	•	•		1,040	860	1,045	865	935	790	1,045	865	790
10 1/2x5x6 1/2	267/127-165	•			1,075	885	1,070	880	960	810	1,070	880	810
10 1/2x6x6 1/2	267/152-165	•			1,340	1,100	1,190	1,000	970	795	1,430	1,050	950
10 1/2x7x6 1/2	267/178-165	•			1,600	1,310	1,430	1,200	1,160	950	1,430	1,050	955
12x6x6 1/2	305/152-165	•			1,540	1,265	1,375	1,155	1,155	915	1,650	1,210	1,100
<b>8"</b>													
10x3x8	254/76-203	•	•		530	435	470	395	-	-	630	415	380
12x4x8	305/102-203	•	•		905	745	810	680	540	970	710	645	485

**PNS 85**

**PNS 85**  
NON MARKING



TYRE SPECIFICATIONS (INCHES)													
Tyre load capacity (kg) at max. speed mph (kmph)													
IMPERIAL SIZE					Counterbalanced-fork-lift-trucks, up to						On Other Vehicles, up to		
TYRE SIZE (INCHES)	TYRE SIZE (MM)	TREAD			6 mph (10 mph)		10 mph (16 mph)		16 mph (25 mph)		3.75 mph	6 mph	10 mph
		PNS 85	PNM 85	PNT 85	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 kmph	10 kmph	16 kmph
12x4 1/2x8	305/114-203	•			1,040	855	930	780	780	620	1,115	820	745
12x5x8	305/127-203	•	•		1,190	980	1,065	890	865	710	1,275	1,160	850
12x5 1/2x8	305/140-203				1,340	1,100	1,195	1,005	1,005	795	1,435	1,050	955
12x6 1/2x8	305/165-203	•	•		1,620	1,330	1,450	1,215	1,215	965	1,740	1,275	1,160
13x3x8	330/76-203	•			710	590	605	505	-	-	810	530	485
13x3 1/2x8	330/89-203	•	•		785	645	790	650	700	590	790	650	590
13x4 1/2x8	330/114-203	•	•		1,120	920	1,120	920	1,000	840	1,120	920	840
13x5x8	330/127-203	•	•		1,290	1,060	1,290	1,060	1,150	965	1,290	1,060	965
13x5 1/2x8	330/140-203	•	•		1,460	1,200	1,460	1,200	1,300	1,090	1,460	1,200	1,090
13 1/2x4 1/2x8	343/140-203	•	•		1,150	940	1,025	860	835	685	1,225	900	820
13 1/2x5 1/2x8	343/140-203	•	•		1,510	1,240	1,345	1,130	1,095	895	1,620	1,185	1,080
14x4 1/2x8	356/114-203	•	•		1,170	960	1,170	960	1,045	875	1,170	960	875
<b>10"</b>													
14x5x10	356/157-254	•	•		1,335	1,100	1,195	1,000	1,000	795	1,430	1,050	995
15 1/2x5x10	394/127-254	•	•		1,470	1,210	1,470	1,210	1,315	1,100	1,470	1,210	1,100
15 1/2x6x10	394/152-254	•	•		1,870	1,530	1,665	1,400	1,355	1,110	1,995	1,465	1,330
<b>10</b>													
14x5x10	356/127-254	•	•		1,335	1,100	1,195	1,000	1,000	795	1,430	1,050	995
15 1/2x5x10	394/127-254	•	•		1,470	1,210	1,470	1,210	1,315	1,100	1,470	1,210	1,100
15 1/2x6x10	394/152-254	•	•		1,870	1,530	1,665	1,400	1,355	1,110	1,995	1,465	1,330
<b>10 1/2"</b>													
16x5x10 1/2	406/127-267	•	•	•	1,510	1,240	1,510	1,240	1,345	1,130	1,510	1,240	1,130
16x6x10 1/2	406/152-267	•	•	•	1,915	1,570	1,910	1,570	1,710	1,435	1,910	1,570	1,435
16x7x10 1/2	406/178-267	•	•		2,325	1,910	2,325	1,910	2,070	1,740	2,325	1,910	1,740
<b>11 1/4"</b>													
15x4x11 1/4	381/102-286	•	•		1,065	880	1,065	870	950	795	1,065	870	795
15x5x11 1/4	381/127-286	•	•		1,390	1,145	1,390	1,140	1,240	1,040	1,390	1,140	1,040
15x6x11 1/4	381/152-286	•	•		1,715	1,410	1,715	1,410	1,530	1,285	1,715	1,410	1,285
15x7x11 1/4	381/178-286	•	•		2,055	1,690	1,835	1,545	1,495	1,225	2,205	1,615	1,470
16x5x11 1/4	406/127-286	•	•		1,455	1,195	1,460	1,195	1,300	1,090	1,460	1,195	1,090
16x6x11 1/4	406/152-286	•	•		1,815	1,490	1,800	1,495	1,620	1,360	1,815	1,495	1,360

PNM 85



PNM 85

NON MARKING



TYRE SPECIFICATIONS (INCHES)													
Tyre load capacity (kg) at max. speed mph (kmph)													
IMPERIAL SIZE					Counterbalanced-fork-lift-trucks, up to						On Other Vehicles, up to		
TYRE SIZE (INCHES)	TYRE SIZE (MM)	TREAD			6 mph (10 mph)		10 mph		16 mph		3.75 mph	6 mph	10 mph
							(16 mph)		(25 mph)				
		PNS 85	PNM 85	PNT 85	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 kmph	10 kmph	16 kmph
16x7x11 1/4	406/178-286	•	•		2,210	1,815	2,205	1,815	1,965	1,655	2,220	1,815	1,655
16 1/4x5x11 1/4	413/127-286	•	•	•	1,525	1,250	1,530	1,250	1,360	1,145	1,530	1,250	1,145
16 1/4x6x11 1/4	413/152-286	•	•	•	1,920	1,575	1,920	1,580	1,715	1,440	1,920	1,580	1,440
16 1/4x7x11 1/4	413/178-286	•	•		2,315	1,900	2,325	1,900	2,060	1,735	2,325	1,900	1,735
16 1/4x8x11 1/4	413/203-286	•	•		2,710	2,225	2,420	2,030	2,030	1,615	2,905	2,130	1,935
16 1/2x5x11 1/4	419/127-286	•	•		1,545	1,265	1,375	1,155	1,120	920	1,655	1,210	1,100
16 1/2x6x11 1/4	419/152-286	•	•		1,945	1,595	1,735	1,460	1,410	1,155	2,080	1,525	1,390
17x5x11 1/4	432/127-286		•		1,520	1,245	1,530	1,250	1,360	1,140	1,530	1,250	1,140
<b>12 1/8"</b>													
16x3 1/2x12 1/8	406/89-308	•	•		1,035	850	920	770	-	-	1,230	810	740
17x4 1/2x12 1/8	432/114-308	•	•		1,370	1,130	1,225	1,030	995	815	1,370	1,130	1,030
17x5x12 1/8	432/127-308	•	•		1,570	1,290	1,570	1,290	1,400	1,180	1,570	1,290	1,180
17x6x12 1/8	432/152-308	•	•		1,980	1,630	1,980	1,630	1,770	1,485	1,980	1,630	1,485
18x5x12 1/8	457/127-308	•	•	•	1,645	1,350	1,640	1,350	1,470	1,230	1,640	1,350	1,230
18x6x12 1/8	457/152-308	•	•	•	2,095	1,720	2,100	1,720	1,870	1,575	2,100	1,720	1,575
18x7x12 1/8	457/178-308	•	•	•	2,550	2,095	2,550	2,100	2,280	1,910	2,550	2,100	1,910
18x8x12 1/8	457/203-308	•	•	•	3,005	2,470	3,000	2,475	2,680	2,250	3,000	2,475	2,250
18x9x12 1/8	457/229-308	•	•	•	3,460	2,840	3,450	2,850	3,090	2,600	3,450	2,850	2,600
<b>15"</b>													
20x8x15	508/203-381	•	•		3,165	2,600	2,825	2,375	2,375	1,885	3,390	1,485	2,260
20x9x15	508/229-381	•	•		3,635	2,985	3,245	2,725	2,725	2,165	3,895	1,855	2,600
21x5x15	533/127-381	•	•		1,840	1,510	1,645	1,380	1,335	1,095	1,970	1,445	1,315
21x6x15	533/152-381	•	•		2,355	1,935	2,105	1,765	1,765	1,390	2,515	1,845	1,680
21x7x15	533/178-381	•	•	•	2,870	2,355	2,875	2,350	2,560	2,150	2,875	2,350	2,150
21x8x15	533/203-381	•	•	•	3,385	2,780	3,375	2,775	3,025	2,540	3,375	2,775	2,540
21x9x15	533/229-381	•	•		3,895	3,200	3,900	3,200	3,475	2,920	3,900	3,200	2,920
<b>16"</b>													
20x7x16	508/178-406	•	•		2,650	2,175	2,365	1,990	1,925	1,575	2,780	2,040	1,890
20x8x16	508/203-406	•	•		3,010	2,470	2,685	2,255	2,255	1,790	3,225	2,365	2,150
20x9x16	508/229-406	•	•		3,445	2,830	3,075	2,580	2,580	2,050	3,690	2,705	2,460
22x6x16	559/152-406	•	•		2,440	2,005	2,180	1,830	1,770	1,450	2,600	1,905	1,740

PNT 85



PNT 85

NON MARKING



TYRE SPECIFICATIONS (INCHES)													
Tyre load capacity (kg) at max. speed mph (kmph)													
IMPERIAL SIZE					Counterbalanced-fork-lift-trucks, up to						On Other Vehicles, up to		
TYRE SIZE (INCHES)	TYRE SIZE (MM)	TREAD			6 mph (10 mph)		10 mph (16 mph)		16 mph (25 mph)		3.75 mph	6 mph	10 mph
		PNS 85	PNM 85	PNT 85	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 kmph	10 kmph	16 kmph
22x7x16	559/178-406	•	•		2,975	2,450	2,975	2,450	2,650	2,230	2,975	2,450	2,230
22x8x16	559/203-406	•	•		3,505	2,880	3,500	2,875	3,130	2,625	3,500	2,875	2,625
22x9x16	559/229-406	•	•		4,035	3,315	4,050	3,325	3,600	3,025	4,050	3,325	3,025
22x10x16	559/254-406	•	•		4,570	3,750	4,575	3,750	4,080	3,425	4,575	3,750	3,425
22x12x16	559/305-406	•	•	•	5,630	4,625	5,625	4,625	5,030	4,225	5,625	4,625	4,225
22x14x16	559/356-406	•	•		6,415	5,510	6,715	5,515	5,995	5,035	6,715	5,515	5,035
22x16x16	559/406-406	•	•		7,765	6,380	7,765	6,375	6,930	5,825	7,765	6,375	5,825
<b>17 3/4"</b>													
22x6x17 3/4	559/152-451		•		2,345	1,930	2,095	1,760	1,760	1,395	2,515	1,845	1,675
22x7x17 3/4	559/178-451	•	•		2,825	2,320	2,520	2,120	2,120	1,680	3,025	2,220	2,015
22x8x17 3/4	559/203-451	•	•		3,285	2,695	2,930	2,460	2,460	1,955	3,515	2,580	2,345
22x12x17 3/4	559/305-451		•		5,155	4,235	4,600	3,865	3,865	3,070	5,520	4,050	3,680
<b>20"</b>													
26x6x20	660/152-508	•	•		2,755	2,260	2,460	2,065	2,065	1,640	2,950	2,165	1,965
26x7x20	660/178-508		•		3,370	2,770	3,010	2,530	2,530	2,005	3,610	2,650	2,405
26x8x20	660/203-508	•	•		3,975	3,275	3,550	2,980	2,885	2,365	4,245	3,115	2,850
<b>22"</b>													
28x10x22	711/254-559	•			5,470	4,495	4,885	4,105	4,105	3,255	5,860	4,300	3,905
28x12x22	711/305-559	•	•		6,750	5,545	6,025	5,060	5,060	4,015	7,230	5,305	4,820
28x14x22	711/356-559	•	•		8,030	6,595	7,170	6,020	6,020	4,780	8,600	6,310	5,735
28x16x22	711/406-559	•			9,280	7,625	8,290	6,960	6,960	5,525	9,945	7,295	6,630
<b>30"</b>													
36x10x30	914/254-762	•			6,605	5,425	5,895	4,955	4,795	3,930	7,075	5,190	4,715
40x10x30	1016/225-762	•		•	6,910	5,650	6,010	4,935	6,450	3,995	10,350	6,080	5,860
40x12x30	1016/305-762	•		•	8,760	7,165	7,620	6,255	6,255	5,005	9,100	6,485	5,685
40x14x30	1016/356-762	•		•	10,610	8,680	9,230	7,575	6,060	11,020	7,850	6,890	5,510
40x16x30	1016/406-762	•		•	12,420	10,160	10,805	8,870	7,095	12,905	9,195	8,065	6,450
40x20x30	1016/508-762	•		•	16,120	13,190	14,025	11,515	11,515	9,210	16,745	11,930	10,645

All dimensions are nominal and we reserve the right to make changes any time without notice

TYRE SPECIFICATIONS (mm)													
Tyre load capacity (kg) at max. speed mph (kmph)													
METRIC SIZE				Counterbalanced-fork-lift-trucks, up to							On Other Vehicles, up to		
TYRE SIZE (INCHES)	TYRE SIZE (MM)	TREAD			6 mph (10 mph)		10 mph		16 mph		3.75 mph	6 mph	10 mph
							(16 mph)		(25 mph)				
		PNS 85	PNM 85	PNT 85	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 kmph	10 kmph	16 kmph
<b>75 MM</b>													
	125/50 - 75	•			-	-	-	-	-	-	160	130	110
<b>100 MM</b>													
	150/50-100	•			-	-	-	-	-	-	225	180	160
	150/75-100	•			-	-	-	-	-	-	375	300	230
	150/130 - 100	•			585	480	525	440	425	350	630	460	420
	160/50-100				-	-	-	-	-	-	285	185	170
	170/75-100	•			-	-	-	-	-	-	500	330	280
	200/75-100	•			-	-	-	-	-	-	570	375	345
	200/85-100	•			-	-	-	-	-	-	680	450	410
	200/120-100	•			-	-	-	-	-	-	865	635	575
<b>105 MM</b>													
	200/75-105	•			-	-	-	-	-	-	570	375	345
	200/85-105	•			-	-	-	-	-	-	550	440	330
	200/120-105	•			800	660	715	600	580	475	860	630	570
	200/130-105	•			880	725	785	660	640	525	945	695	630
<b>120 MM</b>													
	180/50-120	•			-	-	-	-	-	-	310	205	185
	180/75-120	•			-	-	-	-	-	-	510	335	305
	180/95-120	•			-	-	-	-	-	-	545	400	365
	230/75-120	•			525	435	470	395	-	-	625	415	375
	230/85-120	•			630	520	565	470	-	-	750	495	450
	270/100-120				780	640	695	585	565	465	835	615	555
	175/50-125	•			-	-	-	-	-	-	295	195	175
<b>140 MM</b>													
	200/50-140	•			-	-	-	-	-	-	350	280	200
	200/75-140	•			-	-	-	-	-	-	550	365	330
	250/75-140	•			560	460	500	420	-	-	665	440	400
	250/100-140	•			765	625	680	575	555	455	815	600	545
	250/130-140	•			1,095	815	950	800	775	635	1,140	835	760
<b>145 MM</b>													
	254/90-145				735	605	655	550	-	-	875	580	525
<b>150 MM</b>													
	220/70-150				-	-	-	-	-	-	560	370	335
	200/90-150				540	440	480	400	-	-	510	410	295
	250/90-150	•			730	600	650	545	-	-	670	545	395
<b>160 MM</b>													
	220/60-160				-	-	-	-	-	-	450	360	270
	265/160-160	•			1,420	1,165	1,265	1,065	1,030	845	1,415	1,160	1,015

TYRE SPECIFICATIONS (INCHES)													
Tyre load capacity (kg) at max. speed mph (kmph)													
IMPERIAL SIZE					Counterbalanced-fork-lift-trucks, up to						On Other Vehicles, up to		
TYRE SIZE (INCHES)	TYRE SIZE (MM)	TREAD			6 mph (10 mph)		10 mph		16 mph		3.75 mph	6 mph	10 mph
							(16 mph)		(25 mph)				
		PNS 85	PNM 85	PNT 85	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 kmph	10 kmph	16 kmph
	267/127-160	•			1,085	890	970	815	785	645	1,160	850	775
	267/160-160	•			1,430	1,175	1,275	1,075	1,040	850	1,535	1,125	1,020
<b>165 MM</b>													
	305/135-165				1,270	1,015	1,115	915	880	695	1,415	1,035	865
<b>169 MM</b>													
	254/120-169	•			940	770	840	705	680	560	1,005	740	670
	255/120-169	•			945	775	845	710	685	560	1,010	740	675
<b>170 MM</b>													
	230/50-170				-	-	-	-	-	-	370	245	225
	230/75-170	•			-	-	-	-	-	-	610	405	375
	230/85-170	•			595	490	530	445	-	-	705	465	475
	250/80-170	•			620	510	555	460	-	-	735	485	440
	250/90-170	•			715	590	640	535	-	-	855	560	495
	250/100-170	•			740	610	660	555	535	440	790	580	545
	250/105-170	•			785	645	700	590	570	465	840	615	560
	260/60-170	•			-	-	-	-	-	-	515	340	310
	260/85-170	•			695	570	620	520	-	-	775	620	465
	260/105-170	•			825	675	735	615	600	490	880	645	590
	260/110-170	•			870	715	780	655	630	520	935	685	620
	260/130-170	•			1,065	875	950	795	770	635	1,140	835	760
	270/105-170				855	705	765	640	620	510	920	675	610
<b>180 MM</b>													
	315/145-180	•			1,480	1,215	1,320	1,110	1,075	880	15,85	1,165	1,055
<b>185 MM</b>													
	290/105-185				905	745	810	680	660	540	970	710	650
<b>190 MM</b>													
	250/50-190	•			-	-	-	-	-	-	395	260	240
	250/60-190	•			-	-	-	-	-	-	500	330	300
	250/70-190	•			-	-	-	-	-	-	600	395	360
	250/85-190	•			630	520	565	470	-	-	745	595	455
	250/100-190	•			690	565	615	520	500	410	740	545	405
	265/85-190 K-WAY	•			690	570	615	515	-	-	825	540	495
	250/100-190				-	-	-	-	-	-	540	355	325
<b>193 MM</b>													
	330/145-193	•			1,535	1,260	1,370	1,150	1,115	915	1,645	1,205	1,095
<b>194 MM</b>													
	330/145-194	•			1,535	1,260	1,370	1,150	1,115	915	1,645	1,205	295
<b>200 MM</b>													
	310/120-200				1,135	930	1,010	850	820	675	1215	890	810

TYRE SPECIFICATIONS (mm)													
Tyre load capacity (kg) at max. speed mph (kmph)													
METRIC SIZE				Counterbalanced-fork-lift-trucks, up to						On Other Vehicles, up to			
TYRE SIZE (INCHES)	TYRE SIZE (MM)	TREAD			6 mph (10 mph)		10 mph		16 mph		3.75 mph	6 mph	10 mph
							(16 mph)		(25 mph)				
		PNS 85	PNM 85	PNT 85	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 kmph	10 kmph	16 kmph
<b>203 MM</b>													
	285/100-203	•			820	675	730	615	595	490	880	645	585
	300/90-203	•			835	685	745	625	-	-	995	655	595
	300/100-203	•			870	715	775	650	630	515	930	685	620
	300/110-203	•			980	805	875	735	710	585	1,050	770	700
	300/120-203	•			1,090	895	975	815	790	650	1,165	855	780
	313/130-203	•			1,260	1,035	1,125	945	915	750	1,350	990	900
<b>210 MM</b>													
	360/110-210				1120	920	1000	840	810	665	1200	880	800
<b>220 MM</b>													
	280/50-220				-	-	-	-	-	-	430	285	260
	285/75-220	•			615	505	545	460	-	-	725	580	420
	285/100-220	•			780	640	695	585	565	465	835	610	555
	310/60-220	•			-	-	-	-	-	-	585	385	350
	310/75-220	•			675	555	600	500	-	-	800	525	485
	310/120-220	•			1,105	905	985	830	800	655	1,215	890	790
	330/120-220	•	•		1,185	975	1,060	890	860	705	1,270	935	850
<b>225 MM</b>													
	343/114-225				1,150	945	1,020	860	835	685	1,230	905	820
<b>230 MM</b>													
	300/100-230				825	680	735	620	600	490	885	650	590
<b>240 MM</b>													
	300/75-240				625	515	560	470	-	-	745	490	445
<b>246 MM</b>													
	380/145-246	•			1,705	1,400	1,520	1,275	1,235	1,015	1,825	1,340	1,215
	380/165-246	•	ML		2,000	1,645	1,785	1,500	1,455	1,190	2,145	1,575	1,430
<b>250 MM</b>													
	340/60-250				-	-	-	-	-	-	625	415	375
<b>270 MM</b>													
	360/60-270				-	-	-	-	-	-	655	430	395
	360/75-270				750	620	670	560	-	-	895	590	535
	360/85-270				885	730	790	660	-	-	1,055	695	635
<b>280 MM</b>													
	350/90-280				900	740	805	615	-	-	1,070	705	645
<b>300 MM</b>													
	450/120-300				1,500	1,230	1,340	1,125	1,090	890	1,605	1,180	1,070
	460/135-300				1,790	1,470	1,595	1,340	1,300	1,065	1,915	1,405	1,275
<b>305 MM</b>													
	400/60-305				-	-	-	-	-	-	700	460	420

TYRE SPECIFICATIONS (INCHES)													
Tyre load capacity (kg) at max. speed mph (kmph)													
IMPERIAL SIZE					Counterbalanced-fork-lift-trucks, up to						On Other Vehicles, up to		
TYRE SIZE (INCHES)	TYRE SIZE (MM)	TREAD			6 mph (10 mph)		10 mph		16 mph		3.75 mph	6 mph	10 mph
							(16 mph)		(25 mph)				
		PNS 85	PNM 85	PNT 85	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 kmph	10 kmph	16 kmph
	405/65-305	•			-	-	-	-	-	-	900	720	540
	405/130-305	•			1,510	1,240	1,345	1,130	1,095	900	1,320	1,185	1,080
	405/260-305	•			3,325	2,730	2,970	2,495	2,415	1,980	3,560	2,610	2,375
	415/75-305	•			820	675	730	610	-	-	975	645	585
	415/90-305	•			1,065	875	950	795	-	-	1,265	835	760
	415/100-305	•			1,115	915	1,000	835	810	665	1,115	915	795
	415/100-305	•			1,115	915	1,115	915	1,000	835	1,115	915	835
	415/200-305				2,590	2,130	2,315	1,945	1,885	1,545	2,780	2,035	1,850
	425/150-305	•			1,910	1,570	1,910	1,570	1,700	1,435	1,910	1,570	1,435
	425/260-305	•			3,625	2,980	3,230	2,720	2,630	2,155	3,625	2,980	2,720
	425/300-305	•			4,245	3,485	4,245	3,485	3,790	3,185	4,245	3,490	3,185
	445/75-305				795	655	710	595	-	-	950	625	570
	450/120-305	•			1,505	1,235	1,340	1,125	1,090	895	1,610	1,180	1,075
	450/260-305	•			3,950	3,245	3,525	2,965	2,870	2,350	4,235	3,105	2,820
	450/300-305	•			4,650	3,820	4,150	3,490	3,375	2,770	4,980	3,655	3,320
<b>335 MM</b>													
	445/75-335				865	710	770	645	-	-	1030	680	615
<b>370 MM</b>													
	500/85-370				1,100	905	980	820	-	-	1,300	1,050	780
	500/100-370				1,270	1,045	1,135	955	925	755	1,360	1,000	910
	500/140-370				1,995	1,640	1,785	1,495	1,450	1,190	2,140	1,570	1,425
	500/280-370				4,535	3,725	4,050	3,405	3,295	2,700	4,860	3,565	3,240
	520/100-370				1,275	1,050	1,140	955	925	760	1,365	1,000	910
	520/120-370	•			1,675	1,375	1,670	1,370	1,490	1,255	1,670	1,370	1,255
	550/150-370	•			2,345	1,930	2,095	1,760	1,705	1,395	2,515	1,845	1,675
<b>410 MM</b>													
	500/65-410				790	650	705	590	-	-	940	620	565
	510/65-410				790	650	705	590	-	-	935	620	560
	540/200-410				3,270	2,685	2,920	2,450	2,375	1,945	3,500	2,570	2,335
	550/120-410				1,750	1,440	1,750	1,440	1,565	1,315	1,750	1,440	1,315
	550/160-410	•			2,550	2,100	2,550	2,100	2,280	1,915	2,550	2,100	1,915
	550/200-410	•			3,355	2,755	2,995	2,515	2,435	1,995	3,595	2,635	2,395
	560/100-410				1,350	1,110	1,205	1,010	980	805	1,445	1,060	965
	610/100-410				1,265	1,040	1,130	950	920	755	1,355	995	905
	610/150-410				2,505	2,055	2,505	2,055	2,235	1,880	2,505	2,055	1,880
	620/200-410				3,790	3,110	3,790	3,110	3,380	2,840	3,790	3,110	2,840
	630/180-410				3,300	2,710	2,945	2,475	2,395	1,965	3,535	2,595	2,355
	645/220-410				4,055	3,320	3,530	2,895	2,845	2,315	4,215	3,000	2,635
	645/250-410	•			4,810	3,930	4,810	3,930	4,180	3,430	4,810	3,930	3,430



TYRE SPECIFICATIONS (mm)													
Tyre load capacity (kg) at max. speed mph (kmph)													
METRIC SIZE				Counterbalanced-fork-lift-trucks, up to						On Other Vehicles, up to			
TYRE SIZE (INCHES)	TYRE SIZE (MM)	TREAD			6 mph (10 mph)		10 mph		16 mph		3.75 mph	6 mph	10 mph
							(16 mph)		(25 mph)				
		PNS 85	PNM 85	PNT 85	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	6 kmph	10 kmph	16 kmph
	645/300-410	•			6,060	4,960	6,060	4,960	5,275	4,330	6,060	4,960	4,330
	645/350-410				7,315	5,985	6,365	5,225	4,180	7,600	5,415	4,750	3,800
<b>480 MM</b>													
	645/200-480	•			3,865	3,175	3,865	3,175	3,450	2,900	3,865	3,175	2,900
	645/250-480	•			4,955	4,065	4,810	3,950	4,215	3,525	4,995	3,985	3,605
	660/203-480	•			3,695	3,025	3,215	2,640	2,590	2,110	3,840	2,730	2,400
	660/250-480	•			4,785	3,915	4,160	3,415	3,355	2,735	4,970	3,540	3,105
	660/280-480	•			5,480	4,480	4,765	3,915	3,840	3,130	5,690	4,055	3,555
	670/200-480				3,675	3,005	3,200	2,625	2,575	2,100	3,820	2,720	2,385
<b>485 MM</b>													
	705/180-485				3,590	2,950	3,205	2,695	2,610	2,135	3,845	2,820	2,565
	710/200-485				3,830	3,135	3,335	2,735	2,685	2,190	3,980	2,835	2,490
<b>500 MM</b>													
	760/250-500	•			5,440	4,450	4,730	3,885	3,815	3,110	5,650	4,025	3,530
<b>559 MM</b>													
	840/356-559				9,100	7,445	7,920	6,500	6,380	5,200	9,455	6,735	5,910
<b>670 MM</b>													
	920/250-670	•			6,280	5,140	5,465	4,485	4,405	3,590	6,525	4,650	4,080
	920/400-670	•			11,300	9,245	9,830	8,070	7,925	6,455	11,740	8,365	7,335
	920/500-670	•			11,300	9,245	9,830	8,070	7,925	6,455	11,740	8,365	7,335

All dimensions are nominal and we reserve the right to make changes any time without notice