



This page includes
Solid Tires | **SOLID RESILIENTS**

SOLID RESILIENTS

TYRE SIZE	TYRE SIZE (METRIC)	RIM	TREAD	Tread Patterns					Tyre load capacity on fork lifts, kg at 25kmph	
				TLL 50	TLR 50	TLS 50	TPL 60	TPA 80	Load Wheel	Steer Wheel
4"										
3.00 - 4		2.10	RIB		•		•		260	195
3.50 - 4		2.10	RIB		•		•		260	195
4.00 - 4		2.50/3.00	LUG/RIB	•	•		•		535	412
5"										
3.00 - 5*		2.10	LUG	•					435	335
3.50 - 5		3.00	LUG	•					900	690
6"										
3.00 - 5*	140/55-6	4.50	LUG	•					1,075	825
8"										
4.00 - 8		2.50/2.75/3.00	LUG / RIB	•	•		•		950	730
4.00 - 8		3.00	MOULD ON RIB		•		•		950	730
4.00 - 8		3.75	RIB		•		•		950	730

TLL 50



TLL 50

NON MARKING



TYRE SIZE	TYRE SIZE (METRIC)	RIM	TREAD	Tread Patterns					Tyre load capacity on fork lifts, kg at 25kmph	
				TLL 50	TLR 50	TLS 50	TPL 60	TPA 80	Load Wheel	Steer Wheel
4.00 - 8		3.75	MOULD ON RIB		•		•		1,010	775
12x3 1/2 - 8		3.00	SM			•	•		850	650
	100/50-8	3.00	SM			•	•		1,000	770
	100/50-8	2.50	SM			•	•		1,000	770
	100/80-8	2.50	MOULD ON RIB			•	•		1,000	770
15x4 1/2 - 8	125/75-8	2.50	RIB / SM		•	•	•		1,040	800
15x4 1/2 - 8	125/75-8	3.00	LUG / RIB / SM	•	•	•	•		1,040	800
15x4 1/2 - 8	125/75-8	3.00	MOULD ON RIB		•		•		1,040	800
15x4 1/2 - 8	125/75-8	3.25	LUG / SM	•		•	•		1,040	800
5.00 - 8		3.00	LUG / RIB / SM	•	•	•	•		1,415	1,090
5.00 - 8		3.50	LUG	•					1,415	1,090
5.00 - 8		3.75	RIB		•		•		1,415	1,090
16x6 - 8	150/75 - 8	4.33	LUG	•			•		1,270	975
17x7 - 8		4.33	SM			•	•		2,000	1,540
18x7 - 8	180/70 - 8	4.33	LUG/RIB/SM	•	•	•	•		2,145	1,650
9										
	200/50 - 10	6.50	LUG/SM	•		•	•		2,470	1,900
6.50 - 10		5.00/5.50	LUG/SM	•		•	•		2,340	1,800

TLR 50



TLS 50



TYRE SIZE	TYRE SIZE (METRIC)	RIM	TREAD	Tread Patterns					Tyre load capacity on fork lifts, kg at 25kmph	
				TLL 50	TLR 50	TLS 50	TPL 60	TPA 80	Load Wheel	Steer Wheel
7.50 - 10*		5.00/5.50	LUG	•					3,070	2,360
23x9 - 10	225/75 - 10	6.50	LUG	•			•		3,160	2,430
12"										
4.50 - 12		3.00	LUG	•					2,340	1,800
7.00 - 12		5.00	LUG	•			•		2,920	2,240
23x10 - 12	250/60 - 12	8.00	LUG	•			•		3,770	2,900
23x12 - 12	315/45 - 12	10.00	LUG	•					4,485	3,450
27x10 - 12	250/75 - 12	8.00	LUG	•			•		3,900	3,000
13"										
23x5 - 13		3.75	LUG	•					1,495	1,150
15"										
5.50 - 15		4.50	LUG	•			•		5,357	4,123
6.00 - 15		4.50	LUG	•			•		6,008	4,619
7.00 - 15		5.50/6.00	LUG	•			•		3,545	2,725
7.50 - 15		5.50/6.00/6.50	LUG	•					3,900	3,000
8.15 - 15 (28x9 - 15)	225/75 - 15	7.00	LUG/SM	•		•	•		3,445	2,650
8.25 - 15		5.50/6.00/6.50	LUG/SM	•		•	•		4,770	3,650
2.50 - 15	250/70 - 15	7.00/7.50	LUG/SM	•		•	•		4,745	3,650

TPL 60



SOLO



TYRE SIZE	TYRE SIZE (METRIC)	RIM	TREAD	Tread Patterns					Tyre load capacity on fork lifts, kg at 25kmph	
				TLL 50	TLR 50	TLS 50	TPL 60	TPA 80	Load Wheel	Steer Wheel
3.00 - 15	315/70 - 15	8.00	LUG/SM	•		•	•		5,850	4,500
28x12.5 - 15	355/45-15	9.75	LUG	•			•		5,525	4,250
	355/65-15*	9.75	LUG	•					7,000	5,450
	400/60-15	11.00	LUG	•					8,970	6,900
16"										
6.50 - 16		5.50	SM			•	•		3,050	2,350
7.50 - 16		5.50/6.00/6.50	LUG	•					3,900	3,000
7.50 - 16 H		5.50/6.00/6.50	LUG	•					3,964	3,050
8.25 - 16		5.50/6.50	LUG	•					4,750	3,650
20"										
7.50 - 20		6.00/6.50	LUG	•					3,900	3,250
8.25 - 20		6.50/7.00	LUG	•					4,380	3,650
	355/50 - 20	10.00	SM			•	•		8,970	6,900
	465/55 - 20	16.00	SM			•	•		10,800	9,000
9.00 - 20		6.50/7.00	LUG/SM	•		•	•		5,400	4,500
10.00 - 20		7.00/7.50/8.00	LUG	•					6,000	5,000
10.00 - 20 SCR		7.00/7.50/8.00	SCR	•					6,000	5,000
10.00 - 20		7.50	SM			•	•		6,000	5,000
10.00 - 20		8.00	LUG					•	6,000	5,000
11.00 - 20		7.50	SM			•	•		6,000	5,000
11.00 - 20		8.00	LUG					•	6,000	5,000

TYRE SIZE	TYRE SIZE (METRIC)	RIM	TREAD	Tread Patterns					Tyre load capacity on fork lifts, kg at 25kmph	
				TLL 50	TLR 50	TLS 50	TPL 60	TPA 80	Load Wheel	Steer Wheel
12.00 - 20		8.00/8.50	LUG/SM	•		•	•		7,560	6,300
14.00 - 20*		10.00	LUG	•					7,870	6,675
14.00 - 20 L*		10.00	LUG	•					7,870	6,675
24"										
12.00 - 24*		8.50/10.00	LUG	•					8,040	6,700
13.00 - 24**		8.50	LUG	•					7,650	6,375
14.00 - 24*		10.00	LUG	•					11,100	9,250
TYRE SIZE	TYRE SIZE (METRIC)	RIM	TREAD	Tread Patterns					Tyre load capacity on fork lifts, kg at 25kmph	
				TLL 50	TLR 50	TLS 50	TPL 60	TPA 80	Load Wheel	Steer Wheel
25"										
14.00 - 25*		10.00/11.25	LUG	•					11,100	9,250
All dimensions are nominal and we reserve the right to make changes any time without notice										
* INDICATES THE SIZES ARE AVAILABLE IN OTHER PATTERN										
** PLEASE REFER APW SPEC SHEET										